according to UK REACH Regulation

## **GRIZZLY DRILLING AND CUTTING OIL 500ml**

Revision date: 25.03.2024 Product code: 11AFX39060003 Page 1 of 15

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

GRIZZLY DRILLING AND CUTTING OIL 500ml
UFI: 4S34-90TR-X00U-42YT

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Lubricant

### 1.3. Details of the supplier of the safety data sheet

Company name: Ferdinand Gross GmbH & Co. KG

Street: Daimlerstr. 8

Place: 70771 Leinfelden-Echterdingen

Telephone: +49 711 1604-0

E-mail: info@schrauben-gross.de Internet: www.schrauben-gross.com

1.4. Emergency telephone 111 NHS (National Health Service)

number:

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### **GB CLP Regulation**

Aerosol 1; H222-H229 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

### **GB CLP Regulation**

Signal word: Danger

Pictograms:





### **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

## **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P273 Avoid release to the environment.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

according to UK REACH Regulation

## Grizzly Bohr-Schneidöl 500ml

Revision date: 25.03.2024 Product code: 11AFX39060003 Page 2 of 15

### Special labelling of certain mixtures

EUH208

Contains 2,6-di-tert-butyl-4-nonylphenol. May produce an allergic reaction.

### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)		•	
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 I	H280		
	Hydrocarbons, C6-C7, n-alkanes, i		10 - < 20 %	
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE H411	H225 H315 H336 H304		
74-98-6	propane		3 - < 5 %	
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 I			
106-97-8	butane		1 - < 3 %	
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 I	H280		
4306-88-1	2,6-di-tert-butyl-4-nonylphenol			0.1 - < 1 %
	224-320-7		01-2120759723-46	
	Skin Sens. 1B, Aquatic Acute 1, Ac	quatic Chronic 1; H317 H400 H410		

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. I	Limits, M-factors and ATE		
	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	10 - < 20 %	
	inhalation: LC50 = > 25,2 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = > 5000 mg/kg			
106-97-8	203-448-7	butane	1 - < 3 %	
	inhalation: LC50 = 658 ppm (gases)			
4306-88-1	224-320-7	2,6-di-tert-butyl-4-nonylphenol	0.1 - < 1 %	
	inhalation: LC5 mg/kg	0 = >10 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = >2000		

### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

## General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an

according to UK REACH Regulation

## Grizzly Bohr-Schneidöl 500ml

Revision date: 25.03.2024 Product code: 11AFX39060003 Page 3 of 15

unconscious person or a person with cramps.

#### After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

### 4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

## Additional information

Danger of bursting container.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

### For non-emergency personnel

First aider: Pay attention to self-protection!

### For emergency responders

Fight fire with normal precautions from a reasonable distance.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

#### 6.3. Methods and material for containment and cleaning up

### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

according to UK REACH Regulation

## Grizzly Bohr-Schneidöl 500ml

Revision date: 25.03.2024 Product code: 11AFX39060003 Page 4 of 15

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

### Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

#### Further information on handling

Avoid contact with skin and eyes.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

#### Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

### Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

### 7.3. Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

according to UK REACH Regulation

## Grizzly Bohr-Schneidöl 500ml

Revision date: 25.03.2024 Product code: 11AFX39060003 Page 5 of 15

### **DNEL/DMEL values**

CAS No	Substance			
DNEL type	DNEL type		Effect	Value
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5%	n-hexane		
Worker DNEL	., long-term	inhalation	systemic	2035 mg/m³
Worker DNEL	., long-term	dermal	systemic	773 mg/kg bw/day
Consumer DN	NEL, long-term	inhalation	systemic	608 mg/m³
Consumer DN	NEL, long-term	dermal	systemic	699 mg/kg bw/day
Consumer DN	NEL, long-term	oral	systemic	699 mg/kg bw/day
4306-88-1	2,6-di-tert-butyl-4-nonylphenol			
Worker DNEL	., long-term	inhalation	systemic	7,84 mg/m³
Worker DNEL, long-term		dermal	systemic	1,11 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	0,56 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,056 mg/kg bw/day

### **PNEC** values

CAS No	Substance			
Environment	Environmental compartment			
4306-88-1	2,6-di-tert-butyl-4-nonylphenol			
Freshwater		0,000124 mg/l		
Freshwater (intermittent releases)		0,00124 mg/l		
Marine water		0,012 mg/l		
Freshwater sediment		106 mg/kg		
Marine sediment		10,6 mg/kg		
Micro-organisms in sewage treatment plants (STP)		10 mg/l		
Soil		21,1 mg/kg		

### Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift

blood (B)

Urine (U)

### 8.2. Exposure controls

### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

### Individual protection measures, such as personal protective equipment

## Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

EN 166

## Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous

according to UK REACH Regulation

## Grizzly Bohr-Schneidöl 500ml

Revision date: 25.03.2024 Product code: 11AFX39060003 Page 6 of 15

substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

**EN ISO 374** 

#### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

#### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

### **Environmental exposure controls**

Observe legal regulations and provisions.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: red brown
Odour: bitter almonds.

**Test method** 

Melting point/freezing point:

Boiling point or initial boiling point and

-40 °C

boiling range:

Flammability: not applicable

not applicable

Lower explosion limits: 0,6 vol. %
Upper explosion limits: 15 vol. %
Flash point: -80 °C
Decomposition temperature: not determined

pH-Value (at 20 °C): not determined DIN 19268

Water solubility:

The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: not determined

Density (at 20 °C): 0,825 g/cm³ DIN 51757

Relative vapour density: not determined

## 9.2. Other information

### Information with regard to physical hazard classes

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidising.

### Other safety characteristics

Evaporation rate: not determined Solid content: not determined

according to UK REACH Regulation

## Grizzly Bohr-Schneidöl 500ml

Revision date: 25.03.2024 Product code: 11AFX39060003 Page 7 of 15

#### **Further Information**

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

The product is stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

### 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

### **Further information**

Do not mix with other chemicals.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in GB CLP Regulation

### Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

## **Acute toxicity**

Based on available data, the classification criteria are not met.

### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

according to UK REACH Regulation

## Grizzly Bohr-Schneidöl 500ml

Revision date: 25.03.2024 Product code: 11AFX39060003 Page 8 of 15

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
	Hydrocarbons, C6-C7, n-	alkanes, isoa	lkanes, cycl	lics, < 5% n-hexane				
	oral	LD50 mg/kg	> 5000	Rat				
	dermal	LD50 3100 mg/kg	> 2800 -	Rat				
	inhalation (4 h) vapour	LC50 mg/l	> 25,2	Rat				
106-97-8	butane							
	inhalation (4 h) gas	LC50	658 ppm	Rat	GESTIS			
4306-88-1	2,6-di-tert-butyl-4-nonylphenol							
	oral	LD50 mg/kg	>2000	Rat				
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2017)	OECD Guideline 402		
	inhalation (4 h) dust/mist	LC50	>10 mg/l	Rat				

#### Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

Contains 2,6-di-tert-butyl-4-nonylphenol. May produce an allergic reaction.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

### STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

May be fatal if swallowed and enters airways.

### Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

### Specific effects in experiment on an animal

No information available.

### Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

### 11.2. Information on other hazards

## **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

### Other information

No information available.

according to UK REACH Regulation

## Grizzly Bohr-Schneidöl 500ml

Revision date: 25.03.2024 Product code: 11AFX39060003 Page 9 of 15

## **SECTION 12: Ecological information**

## 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

according to UK REACH Regulation

## Grizzly Bohr-Schneidöl 500ml

Revision date: 25.03.2024 Product code: 11AFX39060003 Page 10 of 15

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method		
75-28-5	isobutane								
	Acute fish toxicity	LC50 mg/l	91,42	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Hydrocarbons, C6-C7, n-a	alkanes, isc	alkanes, cyc	lics, < 5%	n-hexane				
	Acute fish toxicity	LC50 mg/l	> 1-10	96 h	Pimephales promelas				
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 1-10	48 h	Daphnia magna				
	Fish toxicity	NOEC mg/l	2,045	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)			
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211		
74-98-6	propane								
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
106-97-8	butane								
	Acute fish toxicity	LC50 mg/l	49,9		Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
4306-88-1	2,6-di-tert-butyl-4-nonylph	ienol				·			
	Acute fish toxicity	LC50 mg/l	> 10	96 h	Oncorhynchus mykiss	REACh Registration Dossier	OECD Guideline 203		
	Acute algae toxicity	ErC50 mg/l	> 0,007	72 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	OECD Guideline 201		

according to UK REACH Regulation

Revision date: 25.03.2024					15			
	Acute crustacea toxicity	EC50 mg/l	0,124	48 h	Daphnia magna	REACh Registration Dossier	OECD Guideline 202	
	Acute bacteria toxicity	EC50 mg/l()	> 1000		activated sludge of a predominantly domestic sewag	REACh Registration Dossier	OECD Guideline 209	

#### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane				
	OECD Guideline 301 F 98% 28				
	Easily biodegradable (concerning to the criteria of the OECD)				

#### 12.3. Bioaccumulative potential

The product has not been tested.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	3,4 - 5,2
74-98-6	propane	1,09
106-97-8	butane	1,09
4306-88-1	2,6-di-tert-butyl-4-nonylphenol	> 6,5

### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No information available.

### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

### List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

### List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

according to UK REACH Regulation

## Grizzly Bohr-Schneidöl 500ml

Revision date: 25.03.2024 Product code: 11AFX39060003 Page 12 of 15

### List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

### **SECTION 14: Transport information**

### Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1Marine pollutant:no

Special Provisions: 63, 190, 277, 327, 344, 381,959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

**14.2. UN proper shipping name:** AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1

Special Provisions: A145 A167 A802 Limited quantity Passenger: 30 kg G

Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

according to UK REACH Regulation

## Grizzly Bohr-Schneidöl 500ml

Revision date: 25.03.2024 Product code: 11AFX39060003 Page 13 of 15

### 14.5. Environmental hazards

**ENVIRONMENTALLY HAZARDOUS:** No

### 14.6. Special precautions for user

Warning: Flammable gases.

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 40, Entry 75

Directive 2010/75/EU on industrial

emissions:

No information available.

Directive 2004/42/EC on VOC in

paints and varnishes:

No information available.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Aerosol Directive (75/324/EEC)

### National regulatory information

**Employment restrictions:** Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

## 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 1,5,6.

according to UK REACH Regulation

## Grizzly Bohr-Schneidöl 500ml

Revision date: 25.03.2024 Product code: 11AFX39060003 Page 14 of 15

### Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols Liquefied gas

Flam. Liq: Flammable liquids Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification for inficatos and assa statuation motifica according to CB CE 17.0 galation			
Classification	Classification procedure		
Aerosol 1; H222-H229	On basis of test data		
Asp. Tox. 1; H304	Calculation method		
Skin Irrit. 2; H315	Bridging principle "Aerosols"		
Aquatic Chronic 3; H412	Calculation method		

#### Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
ELILIO00	Contains 2.6 di tart butul 4 nonvinhanal May produce

EUH208 Contains 2,6-di-tert-butyl-4-nonylphenol. May produce an allergic reaction.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product

according to UK REACH Regulation

## Grizzly Bohr-Schneidöl 500ml

Revision date: 25.03.2024 Product code: 11AFX39060003 Page 15 of 15

named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)